

Important information (please keep)!

The **colored marks** on the fabric are production related and will disappear after a few hours of UV exposure.

1. Pull the fabric in the area of the velour tape in shape before fastening, because sewing may cause wrinkles in the area of the velour tape.






2. Always start from the side to attach the fabrics. (from right to left or the other way around)!



3. After attaching the fabric, press it along all velcro® strips once again with help of the operating rod!

Fabric care recommendation:

<p>fabric season</p> 	<p>fabric sunlike</p> 
<p>fabric sunout</p>  <p>do not steam iron</p>	<p>fabric dreamlike -DS</p> 
<p>fabric vuscreen</p> 	<p>Dirt can be rinsed off using a jet of water (no high pressure). If needed sponge down or soft brush with a small amount of mild detergent using max. 30°C (86°F) warm water to clean. Strong friction should be avoided. Then repeatedly rinse the fabric with clean water and allow to dry.</p>

Reimpregnation:

Cause of cleaning, or the ingredients of various cleaning products, a reduction of the water-repellent properties is possible. This cannot be avoided. We recommend reimpregnation after cleaning so that adequate weather protection is subsequently reestablished. Common impregnation products for tent or awning fabrics can be used.

Note when disassembling the velcro® profiles (system HAND - internal static):
First loose the side with the fixed glider, then the side with the movable glider.

